

# PRODUCT DATA



## ANTI SCUFF PASTE 65

### DESCRIPTION

A synergistic combination of solid lubricants in paste form for assembly of all types of metal components. It is blue black in colour with a very low coefficient of friction.

### APPLICATION

Running in lubricant for:-

- Newly machined parts.
- Plain bearings.
- Anti-friction bearings.
- Slide ways and guides.
- Splined shafts.
- Gear faces.

Anti seize for:-

- Threads of fasteners of all metals.
- Especially useful to prevent seizure of and allow nondestructive disassembly of heavy duty steel nuts and bolts exposed to heat load and vibration. Prevents galling of stainless steel threads.

First aid lubricant for:-

- Scored or damaged surfaces.

### BENEFITS

- Easy removal of threaded fasteners.
- Prevents fretting corrosion on splined shafts.
- Facilitates rapid run in of gear teeth.
- Easy removal without scoring of press fitted ball bearings after extended periods of use.

### CHARACTERISTICS

- For ultra high loads.
- Press fitting.
- Metal working, including deep drawing, drilling, tapping, bending, punching and forming.
- High temperatures: -45 to 450°C in limited air 650°C
- Threaded shafts.
- Slides and guides.

### PACKAGING

10kg

---

AVAILABLE FROM

