

PRODUCT DATA



GRAPHITE GREASE

DESCRIPTION

GRAPHITE GREASE is a dark grey / black colour grease, smooth textures homogeneous mixtures of premium quality base oils, calcium-base soap in incorporating finely dispersed lubricating graphite. This product have a strong affinity to metal surfaces and high resistance to water washout. The graphite acts as a solid lubricant, reduces friction, prevents scuffing and seizures even when grease is displaced.

APPLICATION

GRAPHITE GREASE can be used in open gears, pantographs, pump glands, link pins, bushes and linkages, or where plain bearing are badly worn. In addition these greases can also be used in rail and flange lubricating equipment.

This grease is specially developed for the lubrication of pantograph copper strips and contact wires as well as for steam locomotives pins, bogie centres and wire ropes.

SPECIFICATIONS

Appearance	Smooth grey / Black
Thickening agent	Calcium
NLGI Classification	3
Worked penetration	225-245
Drop point °C	90°C
Graphite	20%
Water content % (m/m)	1.5 max
Prompt at CCS No	181-63-1235

PACKAGING

18kg

AVAILABLE FROM



Plot 1691 Lumumba Rd, P O Box 35402, Lusaka
Tel: 021 1 220728 Fax: 021 1 220751
Email : spectra@spectraoil.com

Plot 159, P O Box 21086, Cnr Zomba & Nyerere Rds, Kitwe
Tel: 021 2 221612/223724/223743/229708 Fax: 0212 226394
Email : spectrak@spectraoil.com